

WINKLE

GRYB

MATERIAL HANDLING

ULDSA MAGNET



**Introducing the
ULDSA ultra-light
scrap magnet:
reduce downtime
and boost
profitability across
your operations.**

One of the lightest models in its category.

Heavy-duty fabricated steel case.

High-impact resistant manganese steel bottom plate.

Grade 80 high alloy steel chain assembly.

Wear resistant hard-faced pole shoes.

Aluminum wound coil.

Class "H" insulations.

230 volt DC operation.

75% Continuous duty-cycle.

Moisture & shock resistant high-dielectric compound.

WINKLE

GRYB

MATERIAL HANDLING

ULDSA MAGNET

SIZE DIA.	WEIGHT LBS	VOLTAGE DC	RESISTANCE COLD	AMP. COLD	AMP. HOT	KW MAX	DUTY CYCLE	LIFT DATA LBS		
								#1 HEAVY MELT	#2 HEAVY MELT	TURNINGS
30"	850	230	14.39	15.98	11.19	3.68	75%	500	325	200
36"	1,200	230	11.63	19.78	13.84	4.55	75%	750	425	275
40"	1,575	230	7.51	30.63	21.44	7.04	75%	1,150	700	350
48"	2,200	230	5.62	40.93	28.65	9.41	75%	1,800	1,200	550
58"	3,600	230	3.69	62.33	43.63	14.34	75%	2,825	1,850	875